

1Gb SECONDARY PROTECTOR- *DIGITAL STATION SET* PROTECTOR

ORDERING INFORMATION

ITW Linx Part Number	Description
1GSP	Protects one 8-wire (4-pair) digital station line. Using 110 punchdown In/Out.

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing * (MOQ: 12)

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL Secondary (497A)
Grounding Requirements See Technical Reference page 83-84 for additional grounding tips.
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	4.25"
Height.....	4.25"
Depth	1.5"
Weight.....	0.42 lbs
Product Warranty	Lifetime
Connected Equipment Warranty.....	Up to \$50,000

SIGNAL LINE SURGE PROTECTION: (LAN)

Signal Perfect Circuitry	Yes
Fused/Auto-Resettable.....	Yes
Clamping Level	16V
Response Time	1-5 Nanoseconds
Capacitance.....	<5pF
Wires Protected	4-pairs
Termination Type	110 Punchdown



SECONDARY
MODULAR
PROTECTOR

SURGE GATE
SERIES



Features:

- **Auto-Resetting Technology** - PTC resistors open when a surge occurs, protecting your equipment, but unlike other fuses, the PTCs close again once the surge passes. Less downtime, and less service calls.
- **Designed for use in 1000 BASE T 4-pair networks**
- **Expandable System Protection** - SurgeGate Series Base Units and Modules can be attached to expand system protection as your system grows
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product
- **\$50,000 Connected Equipment**

For up-to-date warranty information, please visit our web site at www.itwlinx.com.



Signal Perfect™

