



M2 - ADVANCED SERIES 2-OUTLET DIRECT PLUG-IN SURGE PROTECTOR

ORDERING INFORMATION

ITW Linx Part Number	Description
M2	2-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management.

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing * (MOQ: 24)

Features:

- 2-outlet AC protection
- Direct Plug-in
- Diagnostic indicator lights (2)
- EMI/RFI noise filtration
- Enhanced backlight
- Integrated cable management
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	2
Grounding Requirements	Uses Electrical AC ground
Width	3.5"
Height	5.5"
Depth	2"
Weight	0.74 lbs
Product Warranty	Lifetime

AC SURGE PROTECTION

Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Single Pulse Energy Dissipation	1350 Joules
Peak Impulse Current	52,000 A
EMI/RFI Noise Filtration	50db (99.7%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level	200V Peak, 141 Rms
UL 1449 Rating	400V
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Direct Plug-in
Number of Outlets	2

2 OUTLET DIRECT PLUG-IN SURGE PROTECTOR

M2 SERIES



For up-to-date warranty information, please visit our web site at www.itwlinx.com.



Signal Perfect™

