



MSL-24V-POWER - 12VDC / 24VAC POWER SURGE PROTECTOR

ORDERING INFORMATION

ITW Linx Part Number	Description
MSL-24V-POWER	Protects two power conductors (1-pair). Using 2 #12 screw termination type.

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing * (MOQ: 6)

Features:

- Power protection module protects two power conductors (1 pair) using 2 #12 AWG screw terminals to ensure all conductive paths are protected
- Solid-state protection provides the fastest response to transient voltages (1-5 nanoseconds) by quickly diverting damaging surges to ground

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Grounding Requirements See Technical Reference page 81-98 for additional grounding tips.
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	4.25"
Height.....	4.25"
Depth.....	1.5"
Weight.....	0.42 lbs
Warranty.....	1 Year from Manufacture

DC POWER CIRCUIT PROTECTION

Fuse Rating	2.5A
Max. Clamping Level.....	30VAC / 45VDC
Response Time	1-5 Nanoseconds
Wires Protected	2-Wires, 1-Pair
Termination Type	#12 Gauge Screw Terminals

For up-to-date warranty information, please visit our web site at www.itwlinx.com.

Signal Perfect™



MODULAR PROTECTOR

SECURELINX
SERIES

