

# POWER DISTRIBUTION UNIT

## RM2500 - RACK MOUNTABLE POWER DISTRIBUTION UNIT



### Features:

- 12 AC power outlets (4 Front, 8 Rear), 15 amps
- Power switch (with guard) controls all 12 outlets
- Four front panel, transformer spaced, convenience outlets
- Single-height rack mountable chassis (1U)
- Front panel circuit breaker
- 10-foot power cord
- Power indication light

### ORDERING INFORMATION

ITW Linx Part Number	Description
RM2500	12-outlets, Rack-mountable AC Power Distribution Unit, 12-outlets (4-front, 8 rear). Fits standard 19" Racks / Cabinets. (MOQ 5)

\* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing \*



For up-to-date warranty information, please visit our web site at [www.itwlinx.com](http://www.itwlinx.com).

### TECHNICAL SPECIFICATIONS

#### PRODUCT SPECIFICATIONS:

Agency Approval .....	UL 1363 recognized, Relocatable Power Tap
LED Indicators .....	Yes (1)
Grounding Requirements .....	Uses Electrical AC Ground
.....	#10 AWG for Primary - N/A
.....	#14 AWG for Isolated Loop - N/A
Recommended Grounding Impedance.....	<0.5 Ohm
Width.....	19"
Height.....	1.75" (1U)
Depth .....	4.5"
Weight.....	4.81 lbs
Product Warranty .....	Lifetime
Connected Equipment Warranty .....	N/A

#### SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION .....	N/A
COAX CIRCUIT PROTECTION .....	N/A
LAN CIRCUIT PROTECTION .....	N/A

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

#### AC SURGE PROTECTION:

SurgeGate Plus Circuitry .....	N/A
Protect or Disconnect Circuitry.....	N/A
Thermal Fusing.....	N/A
Catastrophic Surge Circuit .....	N/A
Over/Undervoltage Voltage Protection .....	N/A
Overvoltage Voltage Shutoff .....	N/A
Undervoltage Voltage Shutoff .....	N/A
Single Pulse Energy Dissipation .....	N/A
Peak Impulse Current.....	N/A
EMI/RFI Noise Filtration .....	N/A
Line Voltage.....	120VAC, 50/60Hz
Initial Clamping Level.....	N/A
UL 1449 Rating.....	N/A
Protection Modes.....	N/A
Maximum Current Rating .....	15A (1800W)
Response Time .....	N/A
Plug Configuration .....	Straight
Number of Outlets.....	12 (4 front, 8 rear)
Switched Outlets.....	All
Cord Length.....	10 ft.

**RacMAX<sup>®</sup>**

