

AC PROTECTION



SP6 - ADVANCED SERIES 6-OUTLET SURGE PROTECTOR

Features:

- Six switched AC power outlets
- Diagnostic indicator lights (2)
- Eight foot power cord with right angle plug
- EMI/RFI noise filtration
- Integrated cable management

- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.

ORDERING INFORMATION

ITW Linx Part Number	Description
SP6	6-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management. (MOQ 6)

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing *



For up-to-date warranty information, please visit our web site at www.itwlinx.com.

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	2
Grounding Requirements	Uses Electrical AC ground, Grounding Impedance.....
	N/A
Width.....	4.6"
Height.....	12.5"
Depth	2.9"
Weight.....	2.18 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	N/A

SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION	N/A
COAX CIRCUIT PROTECTION	N/A
LAN CIRCUIT PROTECTION	N/A

AC SURGE PROTECTION

Thermal Fusing.....	Yes
Catastrophic Surge Circuit	Yes
Single Pulse Energy Dissipation	1020 Joules
Peak Impulse Current.....	48,000 A
EMI/RFI Noise Filtration	50db (99.97%)
Line Voltage.....	120V (50/60Hz)
Initial Clamping Level.....	200V Peak, 141 Rms
UL 1449 Rating.....	400V
Protection Modes.....	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Right Angle
Number of Outlets.....	6
Switched Outlets.....	6
Cord Length.....	8'

For more technical information, refer to "TECHNICAL REFERENCE", page(81-98).

Signal Perfect™ - For more information, refer to page 81.



SP6 Series

