



SP6T - ADVANCED SERIES 6-OUTLET SURGE PROTECTOR

ORDERING INFORMATION

| ITW Linx Part Number | Description |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| SP6T | 6-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management. Plus protection for one telephone or DSL line. |

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing * (MOQ: 6)

Features:

- Six switched AC power outlets
- Telephone protection for one voice or DSL line
- Diagnostic indicator lights (2)
- Eight foot power cord with right angle plug
- EMI/RFI noise filtration
- Integrated cable management
- **Lifetime Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

| | |
|---------------------------------------|--------------------------------|
| Agency Approval | UL 1363, 1449 |
| LED Indicators | 2 |
| Grounding Requirements | Uses Electrical AC ground |
| Width / Height / Depth / Weight | 4.6" / 12.5" / 2.9" / 2.28 lbs |
| Product Warranty | Lifetime |

SIGNAL LINE SURGE PROTECTION: (TELCO)

| | |
|-------------------------------------------------------------|-------------------------|
| Signal Perfect Circuitry / Fuseless / Auto-Resettable | yes |
| Clamping Level | 260V |
| Response Time | 1-5 Nanoseconds |
| Capacitance | ~50pF |
| Suppression Modes | Metallic & Longitudinal |
| Wires Protected | 2-wires, 1-pair |
| Termination Type | RJ-11/45 |

AC SURGE PROTECTION

| | |
|----------------------------------------------------------|--------------------|
| Thermal Fusing / Catastrophic Surge Circuit | Yes |
| Single Pulse Energy Dissipation | 1020 Joules |
| Peak Impulse Current | 48,000 A |
| EMI/RFI Noise Filtration | 50db (99.97%) |
| Line Voltage | 120V (50/60Hz) |
| Initial Clamping Level | 200V Peak, 141 Rms |
| UL 1449 Rating | 400V |
| Protection Modes | L-N, L-G, N-G |
| Maximum Current Rating | 15A (1800W) |
| Response Time | 1-5 Nanoseconds |
| Plug Configuration | Right Angle |
| Number of Outlets / Switched Outlets / Cord Length | 6 / 6 / 8' |

4 OUTLET AC PROTECTOR WITH TELEPHONE / DSL

SP6 SERIES



For up-to-date warranty information, please visit our web site at www.itwlinx.com.



Signal Perfect™

