



CAT6-LAN-RJ45



Features:

- Primary and Isolated Loop applications
- Exceeds TIA/EIA Standards 568 and 758 for CAT6 performance
- Solid-state protection for fastest response
- Use between buildings in a campus environment as a building entrance protector or in hostile industrial applications as an isolated loop protector
- **Expandable System Protection** SurgeGate Modules can be attached to one another to expand system protection as your system grows
- **5 Year Product Warranty** This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product
- **\$50,000 Connected Equipment**



TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Grounding Requirement	See Technical Reference at www.itwlinx.com
Recommended Grounding Impedance	<0.5 Ohm
Width / Height / Depth / Weight	4.25" / 4.25" / 1.5" / 0.42 lbs
Product Warranty	5 Years
Connected Equipment Warranty	Up to \$50,000

SIGNAL LINE SURGE PROTECTION: (TELCO)

Signal Perfect Circuitry	Yes
Fused	Yes
Performance Rating	Cat 6
Clamping Level	16V
Response Time	1-5 Nanoseconds
Capacitance	<5pF
Wires Protected	4-pairs
Termination Type	RJ45

ORDERING INFORMATION

Part Number	Description
-------------	-------------

CAT6-LAN-RJ45	
---------------	--