



M2T - ADVANCED SERIES 2-OUTLET DIRECT PLUG-IN SURGE PROTECTOR

ORDERING INFORMATION

ITW Linx Part Number	Description
M2T	2-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management. Plus protection for one telephone or DSL line.

* Questions about ordering? Please contact us at **1-800-336-LINX** / Contact an authorized distributor for pricing * (MOQ: 24)

Features:

- 2-outlet AC protection
- Direct Plug-in
- Telephone protection for one voice or DSL line
- Diagnostic indicator lights (2)
- RJ-11/45 Jacks
- EMI/RFI noise filtration
- Enhanced backlight
- Integrated cable management
- **5 Year Product Warranty** - This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product
- **2 Grounding and Line Faults:**
Power Protection Status=Green Light ON; Ground Status=Green Light ON

TECHNICAL SPECIFICATIONS

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	2
Grounding Requirements	Uses Electrical AC ground
Width / Height / Depth / Weight.....	3.5" / 5.5" / 2" / 0.74 lbs
Product Warranty	5 Years

SIGNAL LINE SURGE PROTECTION: (TEL)

Signal Perfect Circuitry / Fuseless / Auto-Resettable	yes
Clamping Level.....	260V
Response Time	1-5 Nanoseconds
Capacitance.....	<20pF
Suppression Modes	Metallic & Longitudinal
Wires Protected	2-wires, 1-pair
Termination Type	RJ-11/45

AC SURGE PROTECTION

Thermal Fusing / Catastrophic Surge Circuit	Yes
Single Pulse Energy Dissipation	1350 Joules
Peak Impulse Current.....	52,000 A
EMI/RFI Noise Filtration	50db (99.97%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level.....	200V Peak, 141 Rms
UL 1449 Rating.....	400V
Protection Modes.....	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Direct Plug-in
Number of Outlets.....	2

2 OUTLET DIRECT PLUG-IN SURGE PROTECTOR FOR TEL / DSL LINE PROTECTION

M2 SERIES



For up-to-date warranty information, please visit our web site at www.itwlinx.com.



Signal Perfect™

